

# Accella Polyurethane Systems

## Safety Data Sheet

### 1. Identification of Substance:

**Product Name:** Premicote 1500BC Series

**Supplier Identification:**  
Accella Polyurethane Systems

**Address:**  
100 Enterprise Drive  
Cartersville, GA 30120

**Telephone:**  
770-607-0755

**24-Hr. Emergency Phone Number:**  
CHEMTREC (800) 424-9300

**Product Use:** Water-borne acrylic coating

### 2. Hazards Identification:

#### **GHS Ratings:**

Carcinogen 1A Known Human Carcinogen Based on human evidence

#### **GHS Hazards**

H350 May cause cancer

#### **GHS Precautions**

P201 Obtain special instructions before use  
P202 Do not handle until all safety precautions have been read and understood  
P281 Use personal protective equipment as required  
P308+P313 IF exposed or concerned: Get medical advice/attention  
P405 Store locked up  
P501 Dispose of contents/container in accordance with Section 13

**Signal Word:** Danger



**Chronic effects:** None expected.

### 3. Composition/Data on

#### **Components:**

Chemical Name	CAS number	Weight Concentration %
Limestone	1317-65-3	10.00% - 20.00%
Titanium dioxide	13463-67-7	5.00% - 10.00%
Ammonium hydroxide	1336-21-6	0.10% - 1.00%

Quartz	14808-60-7	0.10% - 1.00%
Benzophenone	119-61-9	0.10% - 1.00%
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	0.10% - 1.00%
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	0.10% - 1.00%

#### **4. First Aid Measures:**

**Inhalation:** If symptoms ensue, move to fresh air. If breathing is difficult, give oxygen.

**After Eye Contact:** Rinse opened eye for at least 15 minutes under running water.

Remove contact lenses if present and easy to do so, and continue rinsing.

**After Skin Contact:** Clean affected area with soap and plenty of water.

**After Swallowing:** Consult physician.

**Notes to Physician:** Treat symptomatically

#### **5. Fire Fighting Measures:**

Flash Point: 210°F, 99°C

LEL: N/A

UEL: N/A

Upper and lower explosive limits listed if known.

**Suitable Extinguishing Agents:** Water spray, CO2, Foam, Dry chemical

**Information about Protection against Explosions and Fires:** Closed containers may rupture when exposed to extreme heat.

#### **Dangerous Products of**

**Decomposition:** Oxides of carbon, oxides of nitrogen, and traces of HCN

#### **Protective Equipment:**

Firefighters should wear a pressure demand self-contained breathing apparatus and protective clothing.

#### **6. Accidental Release Measures:**

**Person-Related Safety Precautions:** Avoid contact with skin and eyes.

**Measures for Environmental Protection:** Cover and contain spill with absorbent material. Collect for proper disposal according to local, state, and federal regulations.

Clean up with water.

## 7. Handling and Storage:

**Information for Safe Handling:** Avoid contact with skin or inhalation.

**Storage Requirements:** Store in dry, well ventilated area. Keep containers tightly closed. Store between 60°F-100°F. Material may settle.

## 8. Exposure Controls and Personal Protection:

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Limestone 1317-65-3	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	Not Established	NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust)
Titanium dioxide 13463-67-7	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	Not Established
Ammonium hydroxide 1336-21-6	Not Established	Not Established	Not Established
Quartz 14808-60-7	Not Established	0.025 mg/m <sup>3</sup> TWA (respirable fraction)	NIOSH: 0.05 mg/m <sup>3</sup> TWA (respirable dust)
Benzophenone 119-61-9	Not Established	Not Established	Not Established
Distillates, petroleum, solvent-dewaxed heavy paraffinic 64742-65-0	Not Established	Not Established	Not Established
Distillates, petroleum, solvent-refined heavy paraffinic 64741-88-4	Not Established	Not Established	Not Established

**Engineering Controls:** No specific measures required.

**Ventilation:** No specific measures required if exposure is below any applicable TLV/PEL. Use exhaust ventilation if exceeded.

**General Protective and Hygienic Measures:** Usual precautionary measures should be adhered to when handling chemicals.

### Personal Protective Equipment:

**Respiratory Protection:** None required if work area is properly ventilated.

**Hand Protection:** Protective chemical resistant gloves.

**Eye Protection:** Safety glasses.

**Body Protection:** Protective work clothing. Launder separately.

## 9. Physical and Chemical Properties:

<b>Appearance:</b> Various colored liquid <b>Vapor Pressure:</b> N/A <b>Vapor Density:</b> N/A	<b>Odor:</b> Mild <b>Odor threshold:</b> N/A <b>pH:</b> N/A
--	---

<b>Specific Gravity</b> 1.10 <b>Freezing point:</b> N/A <b>Boiling range:</b> 100 - 3000°C <b>Evaporation rate:</b> N/A <b>Explosive Limits:</b> N/A  <b>Autoignition temperature:</b> N/A	<b>Melting point:</b> N/A <b>Solubility:</b> N/A <b>Flash point:</b> 210°F,99°C <b>Flammability:</b> N/A <b>Partition coefficient (n- N/A octanol/water):</b> <b>Decomposition temperature:</b> N/A
--	--

**10. Stability and Reactivity:**

**Incompatible Materials:** Avoid contact with isocyanates, strong acids, strong bases and oxidizing agents.

**Hazardous Polymerization:** Not expected to occur.

**Dangerous Products of Decomposition:** Oxides of carbon, oxides of nitrogen, traces of HCN.

**11. Toxicological Information:**

**Mixture Toxicity**

**Component Toxicity**

119-61-9                      Benzophenone  
Dermal LD50: 3,535 mg/kg (Rabbit)

**Toxicity Values Listed if Known**

**Acute Toxicity:**

**Eyes:** May cause irritation & burns.

**Skin:** Minor potential for irritation.

**Inhalation:** Liquid may cause irritation.

**Ingestion:** May cause irritation & burns.

**Chronic Effects:** Not expected to cause any adverse chronic health effects.

**Routes of Entry:** Inhalation, ingestion, skin contact, eye contact

**Target Organs:** Respiratory track, eyes, skin

**Chemicals with Known or Possible Carcinogenic Effects:**

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64741-88-4	Distillates, petroleum, solvent-refined heavy paraffinic	.1 to 1.0%	Distillates, petroleum, solvent-refined heavy paraffinic: EU REACH: Present (L)
13463-67-7	Titanium dioxide	5 to 10%	Titanium dioxide: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
119-61-9	Benzophenone	.1 to 1.0%	Benzophenone: IARC: Possible human carcinogen OSHA: listed

64742-65-0	Distillates, petroleum, solvent-dewaxed heavy paraffinic	.1 to 1.0%	Distillates, petroleum, solvent-dewaxed heavy paraffinic: EU REACH: Present (L)
14808-60-7	Quartz	.1 to 1.0%	Quartz: NIOSH: potential occupational carcinogen IARC: Human carcinogen OSHA: listed

## 12. Ecological Information:

**General Information:** Based on experience, no adverse effects are to be expected if correct disposal procedures have been followed as indicated in section 13. Individual component ecotoxicity listed if known.

### Component Ecotoxicity

Ammonium hydroxide	96 Hr LC50 Pimephales promelas: 8.2 mg/L 48 Hr EC50 water flea: 0.66 mg/L; 48 Hr EC50 Daphnia pulex: 0.66 mg/L
Benzophenone	96 Hr LC50 Pimephales promelas: 13.2 - 15.3 mg/L [flow-through]
Distillates, petroleum, solvent-dewaxed heavy paraffinic	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L 48 Hr EC50 Daphnia magna: >1000 mg/L
Distillates, petroleum, solvent-refined heavy paraffinic	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L 48 Hr EC50 Daphnia magna: >1000 mg/L

## 13. Disposal Considerations:

**Recommendation:** Observe local requirements. Dispose of in accordance with local/state/federal regulations.

## 14. Transport Information:

Not classified as a dangerous good according to transport regulations unless specifically cited below:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
---------------	-----------------------------	------------------	----------------------	---------------------

## 15. Regulatory Information:

**OSHA HAZARD COMMUNICATION STANDARD:** This material is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

**SARA 311/312 Hazard Categories:** None.

### California Proposition 65

#### (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute unless otherwise listed:

**Warning: This product contains chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm:**

Benzophenone 119-61-9 0.1 to 1.0 % CARC  
 Quartz 14808-60-7 0.1 to 1.0 % CARC  
 Titanium dioxide 13463-67-7 5 to 10 % CARC

### Massachusetts Right To Know List:

Quartz 14808-60-7 0.1 to 1.0 %

Titanium dioxide 13463-67-7 5 to 10 %  
Limestone 1317-65-3 10 to 20 %

**New Jersey Right To Know List:**

Quartz 14808-60-7 0.1 to 1.0 %  
Titanium dioxide 13463-67-7 5 to 10 %  
Limestone 1317-65-3 10 to 20 %

**Pennsylvania Right To Know List:**

Quartz 14808-60-7 0.1 to 1.0 %  
Titanium dioxide 13463-67-7 5 to 10 %  
Limestone 1317-65-3 10 to 20 %

**All Substances Listed on TSCA  
Inventory Unless Noted:**

- None

**16. Other Information:**

Safety Data Sheet issued by Product Safety Department

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Accella Polyurethane Systems. The data on these sheets relates only to the specific material designated herein. Accella Polyurethane Systems assumes no legal responsibility for use or reliance upon this data. It is the user's responsibility to ensure that their activities comply with federal, state, or local laws.

Date revised: 2017-03-07

Reviewer Revision 1

Date Prepared: 3/7/2017